



Surface Mount Escape Square

Code: ES/2/NM/WH/865

Escape Surface EM Downlight c/w 2 lens, IP65, White

CQR Emergency Downlights are available as discreet non-maintained spot lights and our range of Escape surface mount downlights allows for mounting on cable trays / baskets in open ceilings with much higher lumen outputs. The Escape and Spots fittings are both available in black and white and come with both corridor and open area interchangeable lens as standard to maximise optionality and ease for our installers.

Features & Benefits

- Emergency Downlight: Surface Mount Escape Square
- Supplied with Open Area Lens (270lm) & Corridor Lens (230lm)
- IP65 rated
- 5 years warranty: full fitting and battery
- Available in black and white
- Self-test functions available
- 20mm conduit entry points
- Ideal for restaurants & large open areas



Technical Data

IP Rating	65
-----------	----

Electrical

Battery	LiFePO4 3.2V 3000mAh
Voltage / Frequency	AC 220-240V 50/60Hz
Running Current (A)	0.017
Charging Power (W)	2
Emergency Power (W)	2
Power Factor	0.39
Inrush Current (A / us)	3
Electrical Class	2

Features

Mounting Method	Surface
-----------------	---------

Photometric Data

Emergency Mode Lumens	Open – 280 / Corridor – 230
CCT (K)	6500
Beam Angle	Open – 150° / Corridor – 80x30°
Lumen Maintenance L80 (Hrs)	50000
CRI	80

Emergency

Emergency Duration (Hrs)	3
Maintained / Non-Maintained	Non-Maintained
Self-Test	No

Mechanical

Mounting Method	Surface
Housing Material	Polycarbonate
Dimensions (LxWxH mm)	155x155x46

Warranty

Product Warranty	5
------------------	---



