



Downlight Spot: Recessed

Code: SP/1/NM/WH/865

WHITE - Spot LED Emergency Downlight, c/w open area & corridor lens

CQR Emergency Downlights are available as discreet non-maintained spot lights and our range of Escape surface mount downlights allows for mounting on cable trays / baskets in open ceilings with much higher lumen outputs. The Escape and Spots fittings are both available in black and white and come with both corridor and open area interchangeable lens as standard to maximise optionality and ease for our installers.

Features & Benefits

- Emergency Downlight Spot: Recessed
- Supplied with Open Area Lens (120lm) and Corridor Lens (130lm) as standard
- Foldable converter: easy to install
- Non-maintained fitting
- 5 years warranty: full fitting and battery
- Available in black and white
- Self-test functions available



Technical Data

IP Rating	20
-----------	----

Electrical

Battery	LiFePO4 3.2V 1500mAh
Voltage / Frequency	AC 220-240V 50/60Hz
Running Current (A)	0.01
Charging Power (W)	1.2
Emergency Power (W)	1
Standby Power (W)	0.4
Power Factor	0.34
Inrush Current (A / us)	3
Electrical Class	2

Features

Mounting Method	Recessed
-----------------	----------

Photometric Data

Emergency Mode Lumens	Open – 120 / Corridor - 130
CCT (K)	6500
Beam Angle	Open – 165° / Corridor – 160 x 50°
Lumen Maintenance L80 (Hrs)	50000
CRI	80

Emergency

Emergency Duration (Hrs)	3
Maintained / Non-Maintained	Non-Maintained
Test Button	No
Self-Test	No

Mechanical

Mounting Method	Recessed
Housing Material	Polycarbonate
Dimensions (LxWxH mm)	250x36x27
Dimensions (DxH mm)	50x21
Cutout Size (DxH)	40x30



Warranty

Product Warranty

5

