

EVO SLIM MINI


Technical Specification

Product Code: OV9110010EM

Luckinslive 433364821



Description: 10W LED Bulkhead Emergency IP65 CCT White



General Information

Dimensions (mm)	240 (Dia.) x 63 (D)
Materials	Base & Diffuser: Polycarbonate (UV Stabilised)
Colour	White (RAL9016)
Product Weight (Kg)	0.85
Ingress Protection	IP65
Mounting	Ceiling or Wall
Warranty (Years)	5

Luminaire Output


Colour Temperature (K)	3000	4000	6000
Typical Luminous Flux (lm)	850	930	900
Efficacy (lm/W)	70	77	75
Beam Angle (°)	120		
Colour Rendering Index (CRI)	>80		
LED Lifetime (L70) (Hours)	30000		

Supply & Power Information

Continuous Operating Voltage (AC) (Hz)	220-240 (50/60)
Safety Class	II
Circuit Wattage (W)	12
LED Wattage (W)	10
Input Current (mA)	250
Power Factor	>0.9
Driver Information	Integrated
Operating Temperature (°C)	0 to +50
Maximum Critical Temperature (°C)	+80
Input Terminations	4 Pole Push-fit Terminals

Emergency Backup Information

Emergency Luminous Flux (lm)	90
Installation	Can be wired as maintained or non-maintained
Battery Specification	Li-Ion 2000mAh 3.7V
Minimum Duration (Hours)	3
Battery Warranty (Years)	4



OVIA Limited, Scolmore House, Mariner, Lichfield Road Industrial Estate,

Tamworth, Staffordshire, B79 7UL United Kingdom

T: +44 (0)1827 300640

E: sales@oviaUK.com | W: oviaUK.com



Catalogue



Section



DoC



Installation

